



for an excellent finish

Belts, narrow: ZIRCONIT ZR 494 Z

Aggressive zirconia alumina belts for applications with maximum loads and high demands on economy

Product benefits

- Very high stock removal rate and long service life
- Maximum performance through optimized abrasive grit coating process in combination with a robust cloth backing
- Suitable for applications with high grinding pressure
- Excellent for wet and dry grinding and especially economical when grinding aluminum and mild steel

Applications

Sheets, plates, coils:

- Rough grinding of coils, stainless steel plates and high-alloy steels

Forged and cast parts:

- Deburring of sharp-edged forged, stamped and cast parts made of stainless steel, tool steel, titanium, nickel and chrome-cobalt alloys

Tubes, rods, wire:

- Leveling of weld seams on round and square tubes
- Descaling wire

Metal working:

- Flat- and edge grinding of sandwich materials based on metal, polymer and composites (ski edges and bearing surfaces)

Wood working:

- Machine calibration sanding of wood, wood-based material and composite workpieces



Product design

| | |
|-------------|-------------------------------------|
| Type: | ZIRCONIT ZR 494 Z |
| Grain: | Zirconia alumina |
| Bonding: | Resin |
| Backing: | Very heavy, stiff Z-polyester cloth |
| Coating: | Closed |
| Grit range: | # 24/36/40/50/60/80/100/120 |






for an excellent finish

Stock programme Belts, narrow: ZIRCONIT ZR 494 Z (Width x Length)



For current delivery forms and times, please contact your local customer service or use our online service portal "Hermes Connect". Already registered as a customer there?



Very suitable



Suitable