



Product range

HERMES

SANDING SPONGES

PREMIUM, SINGLE-SIDED



PREMIUM, DOUBLE-SIDED



PREMIUM, FOUR-SIDED



Application	Manual fine sanding of wood in preparation for staining and varnishing Intermediate sanding of primers and lacquers of furniture parts Intermediate sanding of primer and filler in automotive paint shops Fine cleaning of metallic surfaces from discoloration		
Product benefits	Good adaptability to contours, radii and shapes Universally applicable: dry, mist-damp or wet	High edge stability Very high adaptability prevents deformation of the workpieces to be sanded Pressure compensating foam layer reduces the risk of sanding through surface coatings Universally applicable: dry, mist-damp or wet	Good adaptability to Contours, radii and shapes Especially suitable for sanding corners and edges in one operation Universally applicable: dry, mist-damp or wet
Abrasive grain	Aluminum oxide	Silicon carbide	Aluminum oxide
Bonding	Resin	Resin	Resin
Backing	Rigid PU foam	Very flexible PU foam	Rigid PU foam
Grit range	P 100, P 180, P 280, P 400	F 60, F 100, F 180, F 220	F 60, F 100, F 180, F 220

STOCK LIST HERMES SANDING SPONGES

DIMENSION [WIDTH X LENGTH X HIGHT]

TYPE / DESCRIPTION	GRIT	CODE	PACKAGING	
			Small packaging unit [pcs]	Large packaging unit [pcs]



70 X 100 X 27 MM

Premium, four-sided		F	60	6005968	250	4500
		F	100	6005969	250	4500
		F	180	6005970	250	4500
		F	220	6006031	250	4500



97 X 123 X 12 MM

Premium, double-sided		F	60	6005817	250	6000
		F	100	6005818	250	6000
		F	180	6005819	250	6000
		F	220	6005820	250	6000



115 X 140 X 5 MM

Premium, single-sided		P	100	6006244	250	10000
		P	180	6006623	250	10000
		P	280	6007277	250	10000
		P	400	6009555	250	10000



PLEASE CONTACT US

Detailed information and literature for download at hermes-abrasives.com.
You will find your direct contact person in the [Contact](#) section.

HERMES Schleifmittel GmbH
Taskoepruestrasse 1 • 22761 Hamburg • Germany
hermes-abrasives.com

